



Goff's Enterprises, Inc.

Manufacturers of the Original Goff Curtain Walls
1228 Hickory Street • Pewaukee, Wisconsin 53072
Phone 800-234-0337 • 262-691-4998 • Fax 262-691-3255
Email sales@goffscw.com • Web www.goffscurtainwalls.com

Dear Valued Customer:

Thank you for purchasing Goff's Shield All!

Below are recommendations. Instructions are printed on the bottle.
If you have any questions or concerns please contact one of our product specialists at 800-234-0337 (M-F 8:00am to 4:30pm CST).

Sincerely,
Goff's Enterprises, Inc.

Spray Gun Recommendations

Conventional spray gun: 1.8-2.0 fluid tip, 40-50 PSI
Gravity feed spray gun: 1.6-2.0 fluid tip, 30-40 PSI
HVLP spray gun: 1.8-2.0 fluid tip, 25-45 PSI
Pressure pot: 10-15 PSI at Pot, 40-45 PSI at gun
Airless: 0.013 orifice, 75-90 PSI

DO NOT FORCE DRY THE SHIELD-ALL!

It will not form a good protective film. Let it air dry.

Shield-All will withstand heated booth bake cycles up to 170 degrees.

How Much Do I Need?

Booths

On average, 1.5 gallons will cover a typical booth, with the dimensions of 14' x 24' x 8'. This will cover the booth with one coat at arm height making the product washable. For a peelable coating, apply 2-3 coats, letting it air dry between coats.

Curtain Walls

On average, one gallon will cover 400 square feet of curtain.

When Should I Reapply Shield-All?

If your through-put is:

- 10 vehicles a month – Re-shield every 90 days
- 20 vehicles a month – Re-shield every 60 days
- 30 vehicles a month – Re-shield every 30 days