

Feature / Benefit	G2 Lite Chain Hoist	G2 Lite Spring Assist	G2 Lite 1800 Series	G2 Lite 3000 Series
Applications:				
Ideal for forklift traffic	--	--	--	--
Ideal for Carwashes	--	--	--	--
Ideal for loading docks	Yes	Yes	Yes	Yes
Suitable for Exterior openings	--	--	--	--
Features:				
Duty Cycles of 40/hrs +	N/A	N/A	Yes	Yes
Duty Cycles of 70/hrs +	N/A	N/A	HDC - Opt*	Yes
Duty Cycles of up to 160/hr	N/A	N/A	--	--
Water & Dustproof Operator	N/A	N/A	--	--
Removable / Replacable panels	Yes	Yes	Yes	Yes
Auto reset after impact	--	--	--	--
Integratable with all control options	N/A	N/A	Yes	Yes
Sizes available to 12' x 12'	Yes	Yes	Yes	Yes
Sizes available to 16' x 16'	--	--	--	--
Speeds 18" / Second +	N/A	N/A	Yes	Yes
Speeds 28" / Second +	N/A	N/A	--	Yes
Speeds 30" / Second +	N/A	N/A	--	Yes
Speeds 36" / Second +	N/A	N/A	--	--
Speeds to 54" / Second	N/A	N/A	--	--
Manual Override	N/A	N/A	--	Yes
Variable Frequency Drive	N/A	N/A	--	--
Available in 110V	N/A	N/A	Yes	Yes
Available in 220V	N/A	N/A	--	--
Windload rated	--	--	--	--
Under Header Mount Available	--	Yes	Yes	--
Projection Mount Available	Yes	Yes	Yes	Yes
Face Mount Available	Yes	Yes	Yes	Yes
Reversing safety beam	N/A	N/A	Opt*	Opt*
Waterproof Infrared safety beam	N/A	N/A	Opt*	Opt*

Feature / Benefit	G2 1800 Series	G2 2800 Series	G2 Harshguard Series	G2 3600 Series	G2 5400 Series
Applications:					
Ideal for forklift traffic	--	--	--	Yes	Yes
Ideal for Carwashes	--	--	Yes	--	--
Ideal for loading docks	Yes	--	--	--	--
Suitable for Exterior openings	Yes	Yes	Yes	Yes	Yes
Features:					
Duty Cycles of 40/hrs +	Yes	Yes	Yes	Yes	Yes
Duty Cycles of 70/hrs +	HDC - Opt*	Yes*	--	Yes	Yes*
Duty Cycles of up to 160/hr	--	--	--	Yes	--
Water & Dustproof Operator	--	--	Yes	--	Yes**
Removable / Replacable panels	Yes	Yes	Yes	Yes	Yes
Auto reset after impact	Yes	Yes	Yes	Yes	Yes
Integratable with all control options	Yes	Yes	Yes	Yes	Yes
Sizes available to 12' x 12'	Yes	Yes	Yes	Yes	Yes
Sizes available to 16' x 16'	Yes	Yes	Yes	Yes	Yes
Speeds 18" / Second +	Yes	Yes	Yes	Yes	Yes
Speeds 28" / Second +	--	Yes	Yes	Yes	Yes
Speeds 30" / Second +	--	Yes	--	Yes	Yes
Speeds 36" / Second +	--	--	--	Yes	Yes
Speeds to 54" / Second	--	--	--	--	Yes
Manual Override	--	Yes	Yes	Yes	Yes
Variable Frequency Drive	--	--	--	--	Yes
Available in 110V	Yes	Yes	Yes	Yes	Yes
Available in 220V	--	Yes	Yes		Yes
Windload rated	Yes	Yes	Yes	Yes	Yes
Under Header Mount Available	Yes	--	--	--	--
Projection Mount Available	Yes	Yes	Yes	Yes	Yes
Face Mount Available	Yes	Yes	Yes	Yes	Yes
Reversing safety beam	Yes	Yes	Yes	Yes	Yes
Waterproof Infrared safety beam	Opt*	Opt*	Yes	Opt*	Yes
			*optional upgrade		