



Goff's Enterprises, Inc.

Manufacturers of the Original Goff's Curtain Walls
700 Hickory Street • Pewaukee, Wisconsin 53072
Phone 800-234-0337 • 262-691-4998 • Fax 262-691-3255
Email sales@goffscw.com • Web www.goffscurtainwalls.com

G-2 HarshGuard Doors Features & Benefits

Product Features

- Automatically re-sets after blow-out
- Safety photo eye
- Wind load rated
- Stainless Steel & Aluminum Components
- Easily replaceable, exchangeable heat sealed panels available in solid vinyl & clear PVC.
- Resistant to all ultraviolet rays and is rot, tear and mildew resistant.
- Meets NFPA 701 and California Fire Marshal Standards for flame retardancy
- Custom fiberglass pultrusions bend if loaded, won't kink or break.
- Vinyl PVC Weather Stripping side seals & baffle.
- Custom aluminum extrusions
- Upper box completely assembled at factory for easy & fast installation.
- Slanted Upper Valance panel made from 18oz. coated vinyl allows water runoff while protecting the roller tube assembly.

Options Available

- Nine Vinyl Color Options: Gray, Black, Blue, Beige, Green, Red, Yellow, Orange and White.
- Outside face mount or inside projection mount available.

Motor Features

- Speed 28" per second, manual override built in
- Integrated Drive Electronics – no separate wall mounted control panel.
- Motor mounts directly to drive shaft – no wall mount required
- Auxiliary Open/Close Logic Points
- Built in Auto Close Timer, Integrated Open/Close Set-Up Control
- Various Control Options ~ Hardwired and RF available to meet specific applications.
- All Components are water/dust tight. Non-corroding and non-oxidizing finish.

Product Benefits

- More throughput due to speed of door
- Save on heat loss during cold months
- Minimize in bay noise
- Control traffic flow
- No air compressor or air cylinder maintenance
- No winter freeze ups
- No damage if struck
- Three year warranty – One year warranty on motor drive mechanism.
- Improves building appearance.
- Interior and/or Exterior Use