# Fast Acting Vinyl Doors for Extreme Conditions!



# **High Speed**

Up to 28" per Second

larshGuard Doors • G2

HarshGuard Doors • G2 HarshGuard Doors

# Low Maintenance

No Cables, Wheels, Springs, or Sewn Construction

# Wind Load Rated

45mph Wind Load\*

### **Durable**

Welded Seams & Fiberglass Windbars

# Reliable

Auto Reset Reverse Safety Feature

#### **Extruded PVC Side Seals**

· Ensures a tight seal along vertical edges

#### **Custom Fiberglass Windbars**

· Bend if loaded, won't break or kink

# **Custom Extruded Aluminum Side Beams**

• 2" deep sleek design

#### **Slanted Upper Box**

· Slanted upper box allows for water run off

#### **Auto Reset**

· Automatically resets after impact or blow out

#### **Reverse Safety Feature**

 Door automatically reverses if beam photo eye is broken.



**Extruded Aluminum Side Beams** 



**Welded Seams** 



**Easily Exchangeable Panels** 

# **Stainless Steel & Aluminum Components**

• Ensure durability against elements and chemicals

\*Wind Load tested on a 10' x 12' solid vinyl Roll-Up Door per ANSI/DASMA 108-2002

# **Operation**



#### 2800 Series

- · 28" per second High **Speed External Operator**
- Completely Water & **Dust Proof**
- Direct Quill Drive to Door
- Sealed Oil Bath Right **Angle Drive**
- Manual Crank Overide in Case of Power Failure
- Nema 4 Control Standard

#### **Options:**

110 Volt - 1 PH Motor

 24/40\*/70† Cycles per hour \*With high duty cycle upgrade †with high duty cycle and fan kit upgrade

#### 208 Volt - 3 PH Motor

120 Cycles Per Hour

# Mounting


#### **Face Mount**

Mount outside to the Face of the building


#### **Projection Mount**

Mount inside the building beyond the existing security door.

- Custom aluminum standoff brackets and corner gussets used to extend the door from the wall past the existing door.
- Vinyl filler panels included to fill the space between the wall and the door.



**Face Mount** 



**Projection Mount** 


# **Control Options**



Nema 1



(Standard)







Remote Control

# **Material & Sizes**

#### Goff's G2 Doors Come in Custom Sizes up to 16' x 16'

- Welded Seam Construction
- Easily Replaceable Panels
- 18 oz Vinyl & 40 Mil Clear PVC

#### 18 oz Vinyl Color Options



Warranty: Goff's Enterprises, Inc warrants all G2 HarshGuard Doors Systems for 3-years – limited warranty on materials and workmanship. Warranty excludes electric motor mechanism; warranty on this is 1 year. Goff's reserves the right to repair or replace warranty items at its discretion.

# **Goff's Other Products**

# Goff's Product line includes a variety of custom made vinyl products.

Other products include High Performance Vinyl & Mesh Doors, Roll-up Curtains, Outdoor & Super Exterior Curtains, Climate Control Curtains, Welding Curtains, Strip Doors, Welding Screens, Privacy Screens, Noise Control Curtains & Screens, Trailer Doors, Manual Bug Blocking Doors, Food Processing Curtains, & More!



**Distributed By** 



700 Hickory Street • Pewaukee, WI 53072 Phone: (262) 691-4998 • 800-234-0337 Fax: (262) 691-3255 • 800-959-0170 www.GoffsCurtainWalls.com sales@goffscw.com Facebook.com/GoffsEnterprises Twitter.com/GoffsEnt











HarshGuard Doors • G2 HarshGuard

Made in U.S.A.