

STRIP DOORS • WELD STRIP DOORS • ACCORDION STRIP DOORS • STRIP DOORS

STRIP DOORS • WELD STRIP DOORS • ACCORDION STRIP DOORS • STRIP DOORS



STRIP DOORS

Easily & Affordably Control Dust, Dirt, Noise, Humidity & Temperature!

- Extremely Durable
- Flame Retardant
- Restricts Air Movement
- Reduces Heat & Cold Loss
- Reduces Noise
- Easy to Install
- Stock & Custom Sizes
- Universal Mounting System
- Multiple Material Options
- Temperature Range from -20° to 150° F

Applications Include:

- Interior & Exterior Doors
- Room Dividers
- Welding Booths
- Loading Docks
- Temperature Controlled Areas



Strip Material Available:

- Standard
- USDA Grade
- Low Temperature
- Ribbed (Ideal for Heavy Traffic Areas)
- Weldview
- Anti-Static
- Orange Safety
- Bug Repellent



Weldview Strip Doors



Accordion Style Strip Doors



Bug Repellent Strip Doors

Stock Strip Doors

Part #	Item (W x H)	% Overlap	Strip Width	Thickness
11266	3' x 7'	50	8"	0.08
11341	3' x 8'	50	8"	0.08
11274	4' x 7'	50	8"	0.08
11275	4' x 8'	50	8"	0.08
11303	5' x 7'	50	8"	0.08
11276	5' x 8'	50	8"	0.08
11304	6' x 7'	50	8"	0.08
11277	6' x 8'	50	8"	0.08
11305	7' x 7'	50	8"	0.08
11295	7' x 8'	50	8"	0.08
11289	7' x 10'	67	12"	0.12
11306	8' x 7'	50	8"	0.08
11286	8' x 8'	50	8"	0.08
11287	8' x 8'	67	12"	0.12
11290	8' x 10'	67	12"	0.12
11307	9' x 7'	50	8"	0.08
11300	9' x 8'	50	8"	0.08
11288	9' x 9'	67	12"	0.12
11291	10' x 10'	67	12"	0.12
11293	10' x 12'	67	12"	0.12
11292	11' x 11'	67	12"	0.12
11294	12' x 12'	67	12"	0.12

Bulk Rolls

Available in strips 4" - 48" wide, 060" - .250" thick, up to 300' in length.



Custom Sizes Available

Application, special circumstances, & size of strip doors needed, may change these suggestions.

Traffic Type	Suggested Use	Strip Overlay	Thickness
Light (8" Strips)	Interior Doors to 10' H and Exterior Doors to 8' H Interior partitions/enclosures, splash barriers, conveyor openings, & assembly lines	50%	.080"
Medium (12" Strips)	Interior Doors & Exterior Doors to 10' to 15' H Noise enclosures, secondary cooler doors	67%	.120"
Heavy (16" Strips)	Heavy Equipment Traffic Doors 14' and Higher. Maximum noise control	50%	.160"

Strip Door Warranty: Goff's Enterprises, Inc. warrants all Strip Door Systems from failure in normal use due to defects in material or workmanship for a period of FIVE years from date of purchase. A LIFETIME warranty on all mounting hardware. Goff's Enterprises may elect to repair or replace defective or damaged goods.

Goff's product line includes a variety of custom made vinyl products.



Distributed By

1/13



700 Hickory Street • Pewaukee, WI 53072
 Phone: (262) 691-4998 • 800-234-0337
 Fax: (262) 691-3255 • 800-959-0170
www.GoffsCurtainWalls.com
sales@goffscw.com
[Facebook.com/GoffsEnterprises](https://www.facebook.com/GoffsEnterprises)
[Twitter.com/GoffsEnt](https://twitter.com/GoffsEnt)



Made in U.S.A.

Stock Ribbed Strip Doors

Part #	Item (W x H)	% Overlap	Strip Width	Thickness
11420	4' x 8'	50	8"	0.08
11421	5' x 8'	50	8"	0.08
11422	6' x 8'	50	8"	0.08
11423	8' x 8'	67	12"	0.12
11424	7' x 10'	67	12"	0.12
11425	8' x 10'	67	12"	0.12
11426	10' x 10'	67	12"	0.12
11427	10' x 12'	67	12"	0.12
11428	12' x 12'	67	12"	0.12

Mounting Hardware

Mount the door flush to the wall or under the jam with universal mounting bracket. Designed for quick installation and faster strip replacement.

Available in 2 models:

MD: For use with pedestrian applications < 12' high. Made from tough, durable polymer compounds, designed for use in cold environments. Constructed with FDA & USDA compliant materials.

HD: For use with motorized traffic applications. Made from heavy-duty structural aluminum.

