



Clean Guard Series

**High Performance Door
for wash down applications**



- ✓ IP-65 Rated, wash down motor
- ✓ Door travels at 20" or 42" per second
- ✓ Includes auto close timer
- ✓ Door panels are chemical resistant
- ✓ Reinforced fiberglass wind bars
- ✓ Door panels meet NFPA-701 and CSFM flame resistance standards
- ✓ VFD provides soft start / stop (42"/sec only)
- ✓ Quick install (only 4 components)

Door Features:

- Non-corrosive, construction grade PVC side guides
- Dual door seals for reduced air infiltration
- NEMA 4 (Up/Down/Stop) controls
- NEMA 4 through beam photo eye
- Stainless steel track transition pieces
- Stainless steel end brackets that support the door roll
- Mildew resistant vinyl door panels are individually replaceable
- Full roll cover to protect the top of the door
- Full width, 40 mil double polished clear PVC window, optional at no cost
- Direct drive motor:
 - 110 volt, 1 phase (40 cycles per hour)
 - 208 volt, 3 phase (120 cycles per hour)
 - 480 volt 3 phase (120 cycles per hour)
- Manual crank override in case of power failure
- No sewn construction on door panels

Applications Include:

- Food Processing Plants
- Contract Packaging Facilities
- Poultry Processing Plants
- Beverage and Food Packaging
- Any wash down required location



IP-65 Motor



Dual Weatherseal

